



Model: H2315

Basic size of
mm

| | |
|----|-----|
| d: | 65 |
| D: | 160 |
| B: | 55 |

The basic rated load is
kN

| | |
|---------------------------|------|
| trends C: | 124 |
| static state Co: | 43 |
| Fatigue load limit Pu: | 2.04 |

Rated rotation speed is
r/min

| | |
|--------------------------------------|------|
| Refer to the speed: | 7500 |
| limit speed: | 5600 |
| Mass bearing + tightening sleeve: | 5.55 |

model

| | |
|-------------------------|-----------|
| bearing: | 2315 K |
| tapered adapter-sleeve: | H231 5 |



Dimensions are
mm

| | |
|---------------------------|-----|
| d ₁ : | 65 |
| d ₃ : | 98 |
| D1 ~ : | 139 |
| B1: | 73 |
| B2: | 15 |
| r _{1,2} the min: | 2.1 |

Shoulder gear and chamfer size
mm

| | |
|-------------------------|-----|
| d _a the max: | 97 |
| d _b the min: | 82 |
| Da the max: | 148 |
| B _a the min: | 7 |
| r _a the max: | 2 |

Calculation coefficient

| | |
|-----|------|
| e: | 0.37 |
| Y1: | 1.7 |
| Y2: | 2.6 |
| Y0: | 1.8 |