



**Model: NCF29/500V**

Basic size of  
 mm

|    |     |
|----|-----|
| d: | 500 |
| D: | 670 |
| B: | 100 |

The basic rated load is  
 kN

|                        |      |
|------------------------|------|
| trends C:              | 2330 |
| static state Co:       | 5000 |
| Fatigue load limit Pu: | 415  |

Rated rotation speed is  
 r/min

|                     |                |
|---------------------|----------------|
| Refer to the speed: | 380            |
| limit speed:        | 450            |
| quality:            | 100            |
| model:              | NCF29/500<br>V |

Dimensions are  
 mm

|                           |       |
|---------------------------|-------|
| d:                        | 500   |
| d <sub>1</sub> ~ :        | 553   |
| D1 ~ :                    | 611   |
| E:                        | 630.9 |
| r <sub>1,2</sub> the min: | 5     |
| r <sub>3,4</sub> the min: | 5     |
| s <sup>1)</sup> :         | 7     |

Shoulder gear and chamfer size  
 mm

|  |     |
|--|-----|
| d <sub>a</sub> the min:                        | 518 |
| d <sub>as</sub> <sup>2)</sup> suggested value: | 544 |
| Da the max:                                    | 652 |
| Db the max:                                    | 652 |
| r <sub>a</sub> the max:                        | 4   |
| r <sub>b</sub> the max:                        | 4   |



