



**Model: NNCL4834CV**

Basic size of  
 mm

|    |     |
|----|-----|
| d: | 170 |
| D: | 215 |
| B: | 45  |

The basic rated load is  
 kN

|                        |      |
|------------------------|------|
| trends C:              | 286  |
| static state Co:       | 655  |
| Fatigue load limit Pu: | 65.5 |

Rated rotation speed is  
 r/min

|                     |                |
|---------------------|----------------|
| Refer to the speed: | 1300           |
| limit speed:        | 1600           |
| quality:            | 3.9            |
| model:              | NNCL4834C<br>V |

Dimensions are  
 mm

|                           |       |
|---------------------------|-------|
| d:                        | 170   |
| d <sub>1</sub> ~ :        | 187   |
| D1 ~ :                    | -     |
| E:                        | 201.3 |
| b <sub>1</sub> :          | 7     |
| k:                        | 4     |
| r <sub>1,2</sub> the min: | 1.1   |
| s <sup>1)</sup> :         | 3     |

Shoulder gear and chamfer size  
 mm

|  |     |
|--|-----|
| d <sub>a</sub> the min:                        | 176 |
| d <sub>as</sub> <sup>2)</sup> suggested value: | -   |
| Da the max:                                    | 209 |
| r <sub>a</sub> the max:                        | 1   |

