



### Model: NNCL4960CV

Basic size of  
mm

|    |     |
|----|-----|
| d: | 300 |
| D: | 420 |
| B: | 118 |

The basic rated load is  
kN

|                        |      |
|------------------------|------|
| trends C:              | 1680 |
| static state Co:       | 3750 |
| Fatigue load limit Pu: | 355  |

Rated rotation speed is  
r/min

|                     |                |
|---------------------|----------------|
| Refer to the speed: | 670            |
| limit speed:        | 800            |
| quality:            | 53             |
| model:              | NNCL4960C<br>V |

Dimensions are  
mm

|                           |       |
|---------------------------|-------|
| d:                        | 300   |
| d <sub>1</sub> ~ :        | 341   |
| D1 ~ :                    | -     |
| E:                        | 385.5 |
| b <sub>1</sub> :          | 9.4   |
| k:                        | 5     |
| r <sub>1,2</sub> the min: | 3     |
| s <sup>1)</sup> :         | 6     |

Shoulder gear and chamfer size  
mm

|  |     |
|--|-----|
| d <sub>a</sub> the min:                        | 315 |
| d <sub>as</sub> <sup>2)</sup> suggested value: | -   |
| Da the max:                                    | 405 |
| r <sub>a</sub> the max:                        | 2.5 |

