



Model: 30238J2

Basic size of
mm

| | |
|----|-----|
| d: | 190 |
| D: | 340 |
| T: | 60 |

The basic rated load is
kN

| | |
|------------------------|------|
| trends C: | 721 |
| static state Co: | 1000 |
| Fatigue load limit Pu: | 95 |

Rated rotation speed is
r/min

| | |
|-------------------------------|-------------|
| Refer to the speed: | 1400 |
| limit speed: | 1800 |
| quality: | 24 |
| model: | 30238J 2 |
| ISO335 Size series (ABMA): | 4GB |

Dimensions are
mm

| | |
|---------------------------|-----|
| d: | 190 |
| d ₁ ~ : | 254 |
| B: | 55 |
| C: | 46 |
| r _{1,2} the min: | 5 |
| r _{3,4} the min: | 4 |
| a: | 63 |

Shoulder gear and chamfer size
mm

| | |
|-------------------------|-----|
| d _a the max: | 224 |
| d _b the min: | 210 |
| Da the min: | 298 |
| Da the max: | 323 |
| Db the min: | 318 |
| Ca the min: | 9 |

| | |
|-------------------------|----|
| Cb the min: | 14 |
| r _a the max: | 4 |
| r _b the max: | 3 |

Calculation coefficient

| | |
|-----|------|
| e: | 0.43 |
| Y: | 1.4 |
| Yo: | 0.8 |