



Model: 32232T179J2/DB32C23

0

Basic size of
mm

| | |
|----|-----|
| d: | 160 |
| D: | 290 |
| T: | 179 |

The basic rated load is
kN

| | |
|-----------------------|------|
| trends C: | 1510 |
| static state Co: | 2800 |
| Fatigue load limit | 265 |
| Pu: | |

Rated rotation speed is
r/min

| | |
|------------------------|--------------------------|
| Refer to the speed: | 1300 |
| limit speed: | 2200 |
| quality: | 52.5 |
| model: | 32232T179J2/DB32C23 0 |

Dimensions are
mm

| | |
|---------------------------|-----|
| d: | 160 |
| d ₁ ~ : | 221 |
| C: | 145 |
| r _{1,2} the min: | 4 |
| r ₅ the min: | 1 |
| a: | 150 |
| C _b the min: | 176 |

Shoulder gear and chamfer size
mm

| | |
|-------------------------|-----|
| d _b the max: | 274 |
| D _b the min: | 17 |
| r _a the max: | 3 |
| r _c the max: | 1 |

Calculation coefficient

| | |
|-----|------|
| e: | 0.43 |
| Y1: | 1.6 |
| Y2: | 2.3 |
| Yo: | 1.6 |