



Model: 22328CCJA/W33VA40

6

Basic size of  
mm

|    |     |
|----|-----|
| d: | 140 |
| D: | 300 |
| B: | 102 |

The basic rated load is  
kN

|                              |      |
|------------------------------|------|
| trends C:                    | 1290 |
| static state<br>Co:          | 1560 |
| Fatigue load<br>limit<br>Pu: | 132  |

Rated rotation speed is  
r/min

|                        |      |
|------------------------|------|
| Refer to the<br>speed: | 1700 |
| limit speed:           | 2200 |
| quality:               | 36.5 |

model

|               |                         |
|---------------|-------------------------|
| Column hole:  | *22328CCJA/W33VA40<br>6 |
| conical bore: |                         |

Dimensions are  
mm

|                           |      |
|---------------------------|------|
| d:                        | 140  |
| d <sub>2</sub> ~ :        | 175  |
| D1 ~ :                    | 247  |
| b:                        | 16.7 |
| k:                        | 9    |
| r <sub>1,2</sub> the min: | 4    |

Shoulder gear and chamfer size  
mm

|                         |     |
|-------------------------|-----|
| d <sub>a</sub> the min: | 157 |
| Da the max:             | 283 |
| r <sub>a</sub> the max: | 3   |

Calculation coefficient

|     |      |
|-----|------|
| e:  | 0.35 |
| Y1: | 1.9  |
| Y2: | 2.9  |
| Y0: | 1.8  |

Allowable acceleration 1)

Only for oil-lubricated bearings

|                |     |
|----------------|-----|
| turn:          | 78g |
| straight line: | 20g |