



Model: 22332CCJA/W33VA40

5

Basic size of
mm

| | |
|----|-----|
| d: | 160 |
| D: | 340 |
| B: | 114 |

The basic rated load is
kN

| | |
|------------------------------|------|
| trends C: | 1600 |
| static state Co: | 1960 |
| Fatigue load limit Pu: | 160 |

Rated rotation speed is
r/min

| | |
|------------------------|------|
| Refer to the speed: | 1500 |
| limit speed: | 1900 |
| quality: | 52 |

model

| | |
|-----------------|--------------------------|
| Column hole: | *22332CCJA/W33VA405 |
| conical bore: | *22332CCKJA/W33VA40 5 |

Dimensions are
mm

| | |
|---------------------------|------|
| d: | 160 |
| d ₂ ~ : | 200 |
| D1 ~ : | 282 |
| b: | 16.7 |
| k: | 9 |
| r _{1,2} the min: | 4 |

Shoulder gear and chamfer size
mm

| | |
|-------------------------|-----|
| d _a the min: | 177 |
| Da the max: | 323 |
| r _a the max: | 3 |

Calculation coefficient

| | |
|-----|------|
| e: | 0.35 |
| Y1: | 1.9 |
| Y2: | 2.9 |
| Y0: | 1.8 |

Allowable acceleration 1)

Only for oil-lubricated bearings

| | |
|----------------|-----|
| turn: | 69g |
| straight line: | 18g |