



Model: 22264CCK/W33

Basic size of
mm

| | |
|------------------|-----|
| d ₁ : | 300 |
| D : | 580 |
| B : | 150 |

The basic rated load is
kN

| | |
|----------------------------|------|
| trends C : | 3600 |
| static state Co : | 4900 |
| Fatigue load limit Pu : | 375 |

Rated rotation speed is
r/min

| | |
|--|------|
| Refer to the speed : | 950 |
| limit speed : | 1300 |
| Mass bearing + tightening sleeve : | 200 |

model

| | |
|------------------------------|-------------------|
| bearing : | *22264CCK/W3 3 |
| tapered adapter- sleeve : | OH3164H |

Dimensions are
mm

| | |
|----------------------------|------|
| d ₁ : | 300 |
| d ₂ ~ : | 379 |
| d ₃ : | 400 |
| D1 ~ : | 513 |
| B ₁ : | 226 |
| B ₂ : | 42 |
| B ₃ : | 56 |
| b : | 22.3 |
| k : | 12 |
| r _{1,2} the min : | 5 |

Shoulder gear and chamfer size

mm

| | |
|----------------|-----|
| d_a the max: | 379 |
| d_b the min: | 338 |
| D_a the max: | 560 |
| B_a the min: | 39 |
| r_a the max: | 4 |

Calculation coefficient

| | |
|-----|------|
| e: | 0.26 |
| Y1: | 2.6 |
| Y2: | 3.9 |
| Yo: | 2.5 |