



Model: 23276CAK/W33

Basic size of
mm

| | |
|------------------|-----|
| d ₁ : | 360 |
| D : | 680 |
| B : | 240 |

The basic rated load is
kN

| | |
|----------------------------|------|
| trends C : | 5850 |
| static state Co : | 9150 |
| Fatigue load limit Pu : | 620 |

Rated rotation speed is
r/min

| | |
|--|-----|
| Refer to the speed : | 500 |
| limit speed : | 750 |
| Mass bearing + tightening sleeve : | 420 |

model

| | |
|------------------------------|-------------------|
| bearing : | *23276CAK/W3 3 |
| tapered adapter- sleeve : | OH3276H |

Dimensions are
mm

| | |
|----------------------------|------|
| d ₁ : | 360 |
| d ₂ ~ : | 471 |
| d ₃ : | 490 |
| D1 ~ : | 581 |
| B ₁ : | 310 |
| B ₂ : | 60 |
| B ₃ : | 77 |
| b : | 22.3 |
| k : | 12 |
| r _{1,2} the min : | 6 |

Shoulder gear and chamfer size

mm

| | |
|----------------|-----|
| d_a the max: | 471 |
| d_b the min: | 405 |
| D_a the max: | 654 |
| B_a the min: | 15 |
| r_a the max: | 5 |

Calculation coefficient

| | |
|-----|------|
| e: | 0.35 |
| Y1: | 1.9 |
| Y2: | 2.9 |
| Yo: | 1.8 |