



Model: 22232CCK/W33

Basic size of
mm

| | |
|------------------|-----|
| d ₁ : | 150 |
| D: | 290 |
| B: | 80 |

The basic rated load is
kN

| | |
|---------------------------|------|
| trends C: | 1000 |
| static state Co: | 1290 |
| Fatigue load limit Pu: | 118 |

Rated rotation speed is
r/min

| | |
|----------------------------------|------|
| Refer to the speed: | 2000 |
| limit speed: | 2800 |
| Mass bearing + return sleeve: | 25 |

model

| | |
|-----------------------|-------------------|
| bearing: | *22232CCK/W3 3 |
| withdrawal sleeve: | AH3132G |

Dimensions are
mm

| | |
|--------------------------------|--------|
| d ₁ : | 150 |
| d ₂ ~ : | 191 |
| D1 ~ : | 250 |
| B ₁ : | 103 |
| B ₂ ¹⁾ : | 108 |
| G: | M170×3 |
| G ₁ : | 16 |
| b: | 13.9 |
| k: | 7.5 |
| r _{1,2} the min: | 3 |

Shoulder gear and chamfer size
mm

d_a the max: 174

D_a the max: 276

r_a the max: 2.5

Calculation coefficient

e: 0.26

Y1: 2.6

Y2: 3.9

Yo: 2.5