



Model: 24048CCK30/W33

Basic size of
mm

| | |
|------------------|-----|
| d ₁ : | 220 |
| D: | 360 |
| B: | 118 |

The basic rated load is
kN

| | |
|-----------------------|------|
| trends C: | 1600 |
| static state Co: | 2700 |
| Fatigue load limit | 228 |
| Pu: | |

Rated rotation speed is
r/min

| | |
|----------------------------------|------|
| Refer to the speed: | 1100 |
| limit speed: | 1600 |
| Mass bearing + return sleeve: | 50.5 |

model

| | |
|-----------------------|-----------------|
| bearing: | *24048CCK30/W33 |
| | 3 |
| withdrawal sleeve: | AOH24048 |

Dimensions are
mm

| | |
|--------------------------------|---------|
| d ₁ : | 220 |
| d ₂ ~ : | 265 |
| D1 ~ : | 316 |
| B ₁ : | 138 |
| B ₂ ¹⁾ : | 153 |
| G: | Tr250×4 |
| G ₁ : | 20 |
| b: | 11.1 |
| k: | 6 |
| r _{1,2} the min: | 3 |

Shoulder gear and chamfer size

mm

d_a the max: 253

D_a the max: 347

r_a the max: 2.5

Calculation coefficient

e: 0.3

Y1: 2.3

Y2: 3.4

Yo: 2.2