



Model: 23064CCK/W33

Basic size of
mm

| | |
|------------------|-----|
| d ₁ : | 300 |
| D: | 480 |
| B: | 121 |

The basic rated load is
kN

| | |
|---------------------------|------|
| trends C: | 2240 |
| static state Co: | 3800 |
| Fatigue load limit Pu: | 285 |

Rated rotation speed is
r/min

| | |
|----------------------------------|------|
| Refer to the speed: | 1100 |
| limit speed: | 1400 |
| Mass bearing + return sleeve: | 89 |

model

| | |
|-----------------------|-------------------|
| bearing: | *23064CCK/W3 3 |
| withdrawal sleeve: | AOH3064G |

Dimensions are
mm

| | |
|--------------------------------|---------|
| d ₁ : | 300 |
| d ₂ ~ : | 360 |
| D1 ~ : | 434 |
| B ₁ : | 149 |
| B ₂ ¹⁾ : | 157 |
| G: | Tr340×5 |
| G ₁ : | 27 |
| b: | 16.7 |
| k: | 9 |
| r _{1,2} the min: | 4 |

Shoulder gear and chamfer size
mm

| | |
|----------------|-----|
| d_a the max: | 335 |
| D_a the max: | 465 |
| r_a the max: | 3 |

Calculation coefficient

| | |
|-----|------|
| e: | 0.23 |
| Y1: | 2.9 |
| Y2: | 4.4 |
| Yo: | 2.8 |