



Model: AOH24068

Basic size of
mm

| | |
|------------------|-----|
| d ₁ : | 320 |
| D: | 520 |
| B: | 180 |

The basic rated load is
kN

| | |
|-----------------------|------|
| trends C: | 3450 |
| static state Co: | 6200 |
| Fatigue load limit | 475 |
| Pu: | |

Rated rotation speed is
r/min

| | |
|----------------------------------|------|
| Refer to the speed: | 750 |
| limit speed: | 1100 |
| Mass bearing + return sleeve: | 160 |

model

| | |
|-----------------------|---------------------|
| bearing: | *24068CCK30/W3 3 |
| withdrawal sleeve: | AOH24068 |

Dimensions are
mm

| | |
|--------------------------------|---------|
| d ₁ : | 320 |
| d ₂ ~ : | 377 |
| D1 ~ : | 453 |
| B ₁ : | 206 |
| B ₂ ¹⁾ : | 225 |
| G: | Tr360×5 |
| G ₁ : | 26 |
| b: | 16.7 |
| k: | 9 |
| r _{1,2} the min: | 5 |

Shoulder gear and chamfer size

mm

d_a the max: 358

D_a the max: 502

r_a the max: 4

Calculation coefficient

e: 0.33

Y1: 2

Y2: 3

Yo: 2