



## Model: C3056K

Basic size of  
mm

d <sub>1</sub> :	260
D :	420
B :	106

The basic rated load is  
kN

trends C :	1860
static state Co :	3100
Fatigue load limit Pu :	250

Rated rotation speed is  
r/min

Refer to the speed :	1200
limit speed :	1600
Mass bearing + tightening sleeve :	65

model

bearing :	*C3056K
tapered adapter-sleeve :	OH3056 H

Dimensions are  
mm

d <sub>1</sub> :	260
d <sub>2</sub> ~ :	328
d <sub>3</sub> :	330
D1 ~ :	389
B <sub>1</sub> :	152
B <sub>2</sub> :	38
r <sub>1,2</sub> the min :	50
s <sub>1</sub> <sup>1)</sup> ~ :	4
s <sub>2</sub> <sup>1)</sup> ~ :	21.3

Shoulder gear and chamfer size  
mm

d <sub>a</sub> the max :	350
d <sub>b</sub> the min :	292

Da the min:	375
Da the max:	405
B <sub>a</sub> the min:	12
Ca <sup>2)</sup> the min:	1.8
r <sub>a</sub> the max:	3

Calculation coefficient

k <sub>1</sub> :	0.121
k <sub>2</sub> :	0.098