



## Model: OH3168H

Basic size of  
mm

d <sub>1</sub> :	320
D:	580
B:	190

The basic rated load is  
kN

trends C:	4900
static state Co:	7500
Fatigue load limit	560
Pu:	

Rated rotation speed is  
r/min

Refer to the speed:	850
limit speed:	1200
Mass bearing + tightening sleeve:	235

model

bearing:	*C3168K
	M
tapered adapter- sleeve:	OH3168H

Dimensions are  
mm

d <sub>1</sub> :	320
d <sub>2</sub> ~ :	405
d <sub>3</sub> :	440
D1 ~ :	517
B <sub>1</sub> :	254
B <sub>2</sub> :	55
r <sub>1,2</sub> the min:	72
s <sub>1</sub> <sup>1)</sup> ~ :	5
s <sub>2</sub> <sup>1)</sup> ~ :	25.9

Shoulder gear and chamfer size  
mm

d <sub>a</sub> the max:	445
-------------------------	-----

d <sub>b</sub> the min:	360
D <sub>a</sub> the min:	490
D <sub>a</sub> the max:	560
B <sub>a</sub> the min:	14
C <sub>a</sub> <sup>2)</sup> the min:	4.2
r <sub>a</sub> the max:	4

#### Calculation coefficient

k <sub>1</sub> :	0.118
k <sub>2</sub> :	0.093