



## Model: C4032K30V

Basic size of  
mm

d <sub>1</sub> :	150
D:	240
B:	80

The basic rated load is  
kN

trends C:	915
static state Co:	1460
Fatigue load limit	140
Pu:	

Rated rotation speed is  
r/min

Refer to the speed:	-
limit speed:	600
Mass bearing + return sleeve:	15

## model

bearing:	*C4032K30
	V
withdrawal sleeve:	AH24032

Dimensions are  
mm

d <sub>1</sub> :	150
d <sub>2</sub> ~ :	181
D1 ~ :	217
B <sub>1</sub> :	95
B <sub>2</sub> <sup>1)</sup> ~ :	106
G:	M170×3
G <sub>1</sub> :	15
r <sub>1,2</sub> the min:	2.1
s <sub>1</sub> <sup>1)</sup> ~ :	18.1
s <sub>2</sub> <sup>1)</sup> ~ :	8.2

Shoulder gear and chamfer size  
mm

d <sub>a</sub> the min:	171
-------------------------	-----

d <sub>a</sub> the max:	195
Da the min:	-
Da the max:	229
Ca <sup>3)</sup> the min:	-
r <sub>a</sub> the max:	2

#### Calculation coefficient

k <sub>1</sub> :	0.109
k <sub>2</sub> :	0.103