



## Model: C4132K30V1

Basic size of  
mm

d <sub>1</sub> :	150
D:	270
B:	109

The basic rated load is  
kN

trends C:	1460
static state Co:	2160
Fatigue load limit Pu:	200

Rated rotation speed is  
r/min

Refer to the speed:	-
limit speed:	300
Mass bearing + return sleeve:	29

## model

bearing:	*C4132K30V1
)	
withdrawal sleeve:	AH24132

Dimensions are  
mm

d <sub>1</sub> :	150
d <sub>2</sub> ~ :	190
D1 ~ :	241
B <sub>1</sub> :	124
B <sub>2</sub> <sup>1)</sup> ~ :	135
G:	M170×3
G <sub>1</sub> :	15
r <sub>1,2</sub> the min:	2.1
s <sub>1</sub> <sup>1)</sup> ~ :	21
s <sub>2</sub> <sup>1)</sup> ~ :	11.1

Shoulder gear and chamfer size  
mm

d <sub>a</sub> the min:	172
-------------------------	-----

d <sub>a</sub> the max:	190
Da the min:	-
Da the max:	258
Ca <sup>3)</sup> the min:	-
r <sub>a</sub> the max:	2

#### Calculation coefficient

k <sub>1</sub> :	0.101
k <sub>2</sub> :	0.105