



## Model: C4136K30V1

Basic size of  
mm

d <sub>1</sub> :	170
D:	300
B:	118

The basic rated load is  
kN

trends C:	1760
static state Co:	2700
Fatigue load limit Pu:	240

Rated rotation speed is  
r/min

Refer to the speed:	-
limit speed:	220
Mass bearing + return sleeve:	38

## model

bearing:	*C4136K30V1
)	
withdrawal sleeve:	AH24136

Dimensions are  
mm

d <sub>1</sub> :	170
d <sub>2</sub> ~ :	211
D1 ~ :	265
B <sub>1</sub> :	134
B <sub>2</sub> <sup>1)</sup> ~ :	145
G:	M190×3
G <sub>1</sub> :	16
r <sub>1,2</sub> the min:	3
s <sub>1</sub> <sup>1)</sup> ~ :	20
s <sub>2</sub> <sup>1)</sup> ~ :	10.1

Shoulder gear and chamfer size  
mm

d <sub>a</sub> the min:	194
-------------------------	-----

d <sub>a</sub> the max:	210
Da the min:	-
Da the max:	286
Ca <sup>3)</sup> the min:	-
r <sub>a</sub> the max:	2.5

#### Calculation coefficient

k <sub>1</sub> :	0.095
k <sub>2</sub> :	0.11