



**Model: 53317**

Basic size of  
 mm

|                  |     |
|------------------|-----|
| d:               | 85  |
| D:               | 150 |
| H <sub>1</sub> : | 58  |

The basic rated load is  
 kN

|                              |     |
|------------------------------|-----|
| trends C:                    | 190 |
| static state Co:             | 465 |
| Fatigue load limit, Pu:      | 16  |
| Minimum load coefficient, A: | 1.1 |

Rated rotation speed is  
 r/min

|                           |      |
|---------------------------|------|
| Refer to the speed:       | 1600 |
| limit speed:              | 2200 |
| Mass bearing + seat ring: | 4.35 |

model




|              |           |
|--------------|-----------|
| bearing:     | 5331<br>7 |
| Seat washer: | U317      |

Dimensions are  
 mm

|                           |      |
|---------------------------|------|
| d:                        | 85   |
| d <sub>1</sub> ~ :        | 150  |
| D1 ~ :                    | 88   |
| D <sub>2</sub> :          | 115  |
| D <sub>3</sub> :          | 155  |
| H:                        | 53.1 |
| C:                        | 17.5 |
| R:                        | 112  |
| s:                        | 43   |
| r <sub>1,2</sub> the min: | 1.5  |

Shoulder gear and chamfer size  
 mm

|                         |     |
|-------------------------|-----|
| d <sub>a</sub> the min: | 124 |
| Da the max:             | 115 |



$r_a$  the max:

1.5