



Model: SNL507TS

diameter of axle

| | |
|---------|----|
| d_a : | 30 |
|---------|----|

bearing block

| | |
|----------|-----|
| A: | 82 |
| A_1 : | 52 |
| H: | 93 |
| H_1 : | 50 |
| H_2 : | 22 |
| J: | 150 |
| L: | 185 |
| N: | 20 |
| N_1 : | 15 |
| G: | 12 |
| quality: | 2.2 |

model

| | |
|--|-------------|
| Bearing seat with seals on both sides: | SNL507TS |
| Component bearing seat: | SNL507-606 |
| seal components: | TSN507S |
| end cap: | ASNH507-606 |

diameter of axle

| | |
|---------|----|
| d_a : | 35 |
|---------|----|

Hole

| | |
|---------|----|
| C_a : | 39 |
| D_a : | 80 |

Total width of the attached seal

| | |
|---------|-----|
| A_2 : | 97 |
| A_3 : | 150 |

Applicable bearings and related parts

| | |
|----------------------------------|--------|
| Automatic centering ball bearing | 1208EK |
| spherical roller | |



| | |
|--|----------------|
| bearing: | |
| tapered adapter-sleeve: | H208 |
| Positioning rings 2 per bearing seat : | FRB10.5/8 0 |
| Automatic centering ball bearing spherical roller bearing CARB bearing: | 2208EK |
| tapered adapter-sleeve: | H308 |
| Positioning rings 2 per bearing seat : | FRB8/80 |