



Model: ASNH508-607

diameter of axle

| | |
|---------|----|
| d_a : | 30 |
|---------|----|

bearing block

| | |
|----------|-----|
| A: | 85 |
| A_1 : | 60 |
| H: | 108 |
| H_1 : | 60 |
| H_2 : | 25 |
| J: | 170 |
| L: | 205 |
| N: | 20 |
| N_1 : | 15 |
| G: | 12 |
| quality: | 2.9 |

model

| | |
|--|--------------|
| Bearing seat with seals on both sides: | SNL607T A |
| Component bearing seat: | SNL508-607 |
| seal components: | TSN607A |
| end cap: | ASNH508-607 |

diameter of axle

| | |
|---------|----|
| d_a : | 35 |
|---------|----|

Hole

| | |
|---------|----|
| C_a : | 41 |
| D_a : | 90 |

Total width of the attached seal

| | |
|---------|-----|
| A_2 : | 102 |
| A_3 : | 150 |

Applicable bearings and related parts

| | |
|----------------------------------|--------|
| Automatic centering ball bearing | 1308EK |
| spherical roller bearing: | |



| | |
|--|---------|
| tapered adapter-sleeve: | H308 |
| Positioning rings 2 per bearing seat : | FRB9/90 |
| Automatic centering ball bearing spherical roller bearing CARB bearing: | 2308EK |
| tapered adapter-sleeve: | H2308 |
| Positioning rings 2 per bearing seat : | FRB4/90 |