



Model: ASNH512-610

diameter of axle

| | |
|---------|----|
| d_a : | 45 |
|---------|----|

bearing block

| | |
|----------|-----|
| A: | 105 |
| A_1 : | 70 |
| H: | 134 |
| H_1 : | 70 |
| H_2 : | 30 |
| J: | 210 |
| L: | 255 |
| N: | 24 |
| N_1 : | 18 |
| G: | 16 |
| quality: | 5.1 |



model

| | |
|--|-------------|
| Bearing seat with seals on both sides: | SNL610TS |
| Component bearing seat: | SNL512-610 |
| seal components: | TSN610S |
| end cap: | ASNH512-610 |

diameter of axle

| | |
|---------|----|
| d_a : | 50 |
|---------|----|

Hole

| | |
|---------|-----|
| C_a : | 44 |
| D_a : | 100 |

Total width of the attached seal

| | |
|---------|-----|
| A_2 : | 107 |
| A_3 : | 165 |

Applicable bearings and related parts

| | |
|----------------------------------|---|
| Automatic centering ball bearing | - |
| spherical roller | - |



| | |
|--|----------------|
| bearing: | |
| tapered adapter-sleeve: | - |
| Positioning rings 2 per bearing seat : | - |
| Automatic centering ball bearing | C2211K |
| spherical roller bearing CARB bearing: | |
| tapered adapter-sleeve: | H311E |
| Positioning rings 2 per bearing seat : | FRB9.5/10 0 |