



Model: TSN515A

diameter of axle

| | |
|---------|----|
| d_a : | 65 |
|---------|----|

bearing block

| | |
|----------|-----|
| A: | 115 |
| A_1 : | 80 |
| H: | 155 |
| H_1 : | 80 |
| H_2 : | 30 |
| J: | 230 |
| L: | 280 |
| N: | 24 |
| N_1 : | 18 |
| G: | 16 |
| quality: | 7 |



model

| | |
|--|--------------|
| Bearing seat with seals on both sides: | SNL515T A |
| Component bearing seat: | SNL515-612 |
| seal components: | TSN515A |
| end cap: | ASNH515-612 |

diameter of axle

| | |
|---------|----|
| d_a : | 65 |
|---------|----|

Hole

| | |
|---------|-----|
| C_a : | 65 |
| D_a : | 160 |

Total width of the attached seal

| | |
|---------|-----|
| A_2 : | 158 |
| A_3 : | 200 |

Applicable bearings and related parts

| | |
|----------------------------------|-------|
| Automatic centering ball bearing | 1315K |
| spherical roller | |



| | |
|----------------------------------|----------|
| bearing: | |
| tapered adapter-sleeve: | H315 |
| Positioning rings | FRB14/16 |
| 2 per bearing seat | 0 |
| : | |
| Automatic centering ball bearing | |
| spherical roller bearing | 2315K |
| CARB bearing: | |
| tapered adapter-sleeve: | H2315 |
| Positioning rings | |
| 2 per bearing seat | FRB5/160 |
| : | |