



**Model: ASNH520-617**

diameter of axle

|         |    |
|---------|----|
| $d_a$ : | 90 |
|---------|----|

bearing block

|          |      |
|----------|------|
| A:       | 160  |
| $A_1$ :  | 110  |
| H:       | 218  |
| $H_1$ :  | 112  |
| $H_2$ :  | 40   |
| J:       | 320  |
| L:       | 380  |
| N:       | 32   |
| $N_1$ :  | 26   |
| G:       | 24   |
| quality: | 17.6 |

model

|  |             |
|--|-------------|
| Bearing seat with seals on both sides: | SNL520TG    |
| Component bearing seat:                | SNL520-617  |
| seal components:                       | TSN520G     |
| end cap:                               | ASNH520-617 |

diameter of axle

|         |    |
|---------|----|
| $d_a$ : | 90 |
|---------|----|

Hole

|         |     |
|---------|-----|
| $C_a$ : | 86  |
| $D_a$ : | 215 |

Total width of the attached seal

|         |     |
|---------|-----|
| $A_2$ : | 199 |
| $A_3$ : | 240 |

Applicable bearings and related parts

|                                  |       |
|----------------------------------|-------|
| Automatic centering ball bearing | 1320K |
| spherical roller                 |       |



|                          |            |
|--------------------------|------------|
| bearing:                 |            |
| tapered adapter-sleeve:  | H320       |
| Positioning rings        | FRB19.5/21 |
| 2 per bearing seat       | 5          |
| :                        |            |
| Automatic centering      |            |
| ball bearing             | 2320K      |
| spherical roller bearing |            |
| CARB bearing:            |            |
| tapered adapter-sleeve:  | H2320      |
| Positioning rings        |            |
| 2 per bearing seat       | FRB6.5/215 |
| :                        |            |