



### 型号：626-2RSL

#### 基本尺寸mm

|    |    |
|----|----|
| d: | 6  |
| D: | 19 |
| B: | 6  |

#### 基本额定负荷kN

|            |      |
|------------|------|
| 动态 C:      | 2.34 |
| 静态 Co:     | 0.95 |
| 疲劳负荷极限 Pu: | 0.04 |

#### 额定转速r/min

|                      |        |
|----------------------|--------|
| 参考转速:                | 80000  |
| 极限转速 <sup>1)</sup> : | 40000  |
| 质量kg:                | 0.0084 |

#### 型号

|         |           |
|---------|-----------|
| 两侧带密封件: | *626-2RSL |
| 一侧带密封件: | *626-RSL  |

#### 尺寸mm

|                      |      |
|----------------------|------|
| d:                   | 6    |
| d1 ~ :               | -    |
| d2 ~ :               | 9.5  |
| D2 ~ :               | 16.5 |
| r <sub>1,2</sub> 最小: | 0.3  |

#### 挡肩及倒角尺寸mm

|                    |      |
|--------------------|------|
| d <sub>a</sub> 最小: | 8.4  |
| d <sub>a</sub> 最大: | 9.4  |
| Da 最大:             | 16.6 |
| r <sub>a</sub> 最大: | 0.3  |

#### 计算系数

|                  |       |
|------------------|-------|
| k <sub>r</sub> : | 0.025 |
| fo:              | 13    |



