



**型号: 624-Z**

**基本尺寸mm**

|    |    |
|----|----|
| d: | 4  |
| D: | 13 |
| B: | 5  |

**基本额定负荷kN**

|            |       |
|------------|-------|
| 动态 C:      | 0.94  |
| 静态 Co:     | 0.29  |
| 疲劳负荷极限 Pu: | 0.012 |

**额定转速r/min**

|                      |        |
|----------------------|--------|
| 参考转速:                | 110000 |
| 极限转速 <sup>1)</sup> : | 53000  |
| 质量kg:                | 0.0031 |

**型号**

|         |        |
|---------|--------|
| 两侧带密封件: | 624-2Z |
| 一侧带密封件: | 624-Z  |

**尺寸mm**

|                      |      |
|----------------------|------|
| d:                   | 4    |
| d1 ~ :               | 6.7  |
| d2 ~ :               | -    |
| D2 ~ :               | 11.2 |
| r <sub>1,2</sub> 最小: | 0.2  |

**挡肩及倒角尺寸mm**

|                    |      |
|--------------------|------|
| d <sub>a</sub> 最小: | 5.8  |
| d <sub>a</sub> 最大: | -    |
| Da 最大:             | 11.2 |
| r <sub>a</sub> 最大: | 0.2  |

**计算系数**

|                  |       |
|------------------|-------|
| k <sub>r</sub> : | 0.025 |
| f <sub>o</sub> : | 7.3   |



