



**型号: 6012-2RS1**

**基本尺寸mm**

|    |    |
|----|----|
| d: | 60 |
| D: | 95 |
| B: | 18 |

**基本额定负荷kN**

|            |      |
|------------|------|
| 动态 C:      | 30.7 |
| 静态 Co:     | 23.2 |
| 疲劳负荷极限 Pu: | 0.98 |

**额定转速r/min**

|                      |      |
|----------------------|------|
| 参考转速:                | -    |
| 极限转速 <sup>1)</sup> : | 4300 |
| 质量kg:                | 0.42 |

**型号**

|         |            |
|---------|------------|
| 两侧带密封件: | *6012-2RS1 |
| 一侧带密封件: | *6012-RS1  |

**尺寸mm**

|                      |      |
|----------------------|------|
| d:                   | 60   |
| d1 ~ :               | 71.3 |
| d2 ~ :               | -    |
| D2 ~ :               | 86.5 |
| r <sub>1,2</sub> 最小: | 1.1  |

**挡肩及倒角尺寸mm**

|                    |    |
|--------------------|----|
| d <sub>a</sub> 最小: | 66 |
| d <sub>a</sub> 最大: | -  |
| Da 最大:             | 89 |
| r <sub>a</sub> 最大: | 1  |

**计算系数**

|                  |       |
|------------------|-------|
| k <sub>r</sub> : | 0.025 |
| fo:              | 16    |



