



型号: C31/500M

基本尺寸mm

| | |
|----|-----|
| d: | 500 |
| D: | 830 |
| B: | 264 |

基本额定负荷kN

| | |
|------------|-------|
| 动态 C: | 7500 |
| 静态 Co: | 12700 |
| 疲劳负荷极限 Pu: | 850 |

额定转速r/min

| | |
|-------|-----|
| 参考转速: | 530 |
| 极限转速: | 750 |
| 质量: | 550 |

型号

| | |
|--------|--------------|
| 轴承圆柱孔: | *C31/500M |
| 圆锥孔: | *C31/500KM2) |

尺寸mm

| | |
|---------------------------------|------|
| d: | 500 |
| d ₂ ~: | 605 |
| D1 ~: | 738 |
| r _{1,2} 最小: | 7.5 |
| s ₁ ¹⁾ ~: | 75.3 |

挡肩及倒角尺寸mm

| | |
|----------------------|-----|
| d _a 最小: | 532 |
| d _a 最大: | 655 |
| Da 最小: | 705 |
| Da 最大: | 798 |
| Ca ²⁾ 最大: | - |
| r _a 最大: | 6 |

计算系数

| | |
|------------------|-------|
| k ₁ : | 0.099 |
| k ₂ : | 0.116 |

