



型号: C3088KMB

基本尺寸mm

| | |
|----|-----|
| d: | 440 |
| D: | 650 |
| B: | 157 |

基本额定负荷kN

| | |
|------------|------|
| 动态 C: | 3750 |
| 静态 Co: | 6400 |
| 疲劳负荷极限 Pu: | 465 |

额定转速r/min

| | |
|-------|------|
| 参考转速: | 750 |
| 极限转速: | 1000 |
| 质量: | 185 |

型号

| | |
|--------|-----------|
| 轴承圆柱孔: | *C3088MB |
| 圆锥孔: | *C3088KMB |

尺寸mm

| | |
|---------------------------------|------|
| d: | 440 |
| d ₂ ~: | 491 |
| D1 ~: | 587 |
| r _{1,2} 最小: | 6 |
| s ₁ ¹⁾ ~: | 19.7 |

挡肩及倒角尺寸mm

| | |
|----------------------|-----|
| d _a 最小: | 463 |
| d _a 最大: | 490 |
| Da 最小: | 565 |
| Da 最大: | 627 |
| Ca ²⁾ 最大: | 1.7 |
| r _a 最大: | 5 |

计算系数

| | |
|------------------|-------|
| k ₁ : | - |
| k ₂ : | 0.105 |

