



**型号: C39/530KM**

**基本尺寸mm**

|    |     |
|----|-----|
| d: | 530 |
| D: | 710 |
| B: | 136 |

**基本额定负荷kN**

|            |      |
|------------|------|
| 动态 C:      | 3550 |
| 静态 Co:     | 7100 |
| 疲劳负荷极限 Pu: | 490  |

**额定转速r/min**

|       |     |
|-------|-----|
| 参考转速: | 670 |
| 极限转速: | 900 |
| 质量:   | 150 |

**型号**

|        |            |
|--------|------------|
| 轴承圆柱孔: | *C39/530M  |
| 圆锥孔:   | *C39/530KM |

**尺寸mm**

|                                 |      |
|---------------------------------|------|
| d:                              | 530  |
| d <sub>2</sub> ~:               | 578  |
| D1 ~:                           | 657  |
| r <sub>1,2</sub> 最小:            | 5    |
| s <sub>1</sub> <sup>1)</sup> ~: | 28.4 |

**挡肩及倒角尺寸mm**

|                      |     |
|----------------------|-----|
| d <sub>a</sub> 最小:   | 548 |
| d <sub>a</sub> 最大:   | 600 |
| Da 最小:               | 640 |
| Da 最大:               | 692 |
| Ca <sup>2)</sup> 最大: | 2.2 |
| r <sub>a</sub> 最大:   | 4   |

**计算系数**

|                  |       |
|------------------|-------|
| k <sub>1</sub> : | 0.129 |
| k <sub>2</sub> : | 0.101 |

